



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Foamed glass – a sustainable load-bearing insulation material

König, K.; Petersen, Rasmus Rosenlund; Østergaard, Martin Bonderup; Yue, Yuanzheng; Suvorov, D.

Publication date:
2018

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

König, K., Petersen, R. R., Østergaard, M. B., Yue, Y., & Suvorov, D. (2018). *Foamed glass – a sustainable load-bearing insulation material*. 54. Abstract from ICG Annual Meeting 2018, Yokohama, Japan.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Foamed glass – a sustainable load-bearing insulation material

Jakob König¹, Rasmus R. Petersen², Martin B. Oestergaard², Yuanzheng Yue², Danilo Suvorov¹

¹Advanced Materials Department, Jozef Stefan Institute, Ljubljana, Slovenia

²Department of Chemistry and Bioscience, Aalborg University, Aalborg, Denmark

Foamed glass is a lightweight material used for thermal and acoustic insulation applications in the construction and other industries. It exhibits several advantages in comparison to insulation materials such as organic foams and mineral wool, e.g., water and steam resistance, freeze-thaw cycle tolerance, excellent chemical and thermal stability, and superior mechanical properties. In the last decade, the possibility of recycling different glass cullets and glassy waste materials into this high value added product has been presented. In this contribution, we present the results of our work focused on improvement of the foamed glass preparation process, improvement of the thermal conductivity and development of closed and open porous foamed glass. Foamed glass can be prepared from a pristine glass or from a cullet. Preparation directly from cullet is more sustainable, however, the properties of thus prepared foamed glass are inferior. In order to ensure superior insulation properties and decreased dependence of the foaming process on the cullet composition, we used a foaming agent–oxidizing agent couple to foam cullets of cathode-ray-tube (CRT) panel, flat and container glass. The density and thermal conductivity of the prepared samples are as low as 100 kg/m³ and 37 mW/(m K), respectively. Analysis of the thermal conductivity of open- and closed-porous foamed glasses will be presented.

References

1. J. König, R.R. Rasmus, Y.Z. Yue, Fabrication of highly insulating foam glass made from CRT panel glass, *Ceram. Int.* 41 (2015) 9793–9800.
2. R.R. Petersen, J. König, Y.Z. Yue, The mechanism of foaming and thermal conductivity of glasses foamed with MnO₂, *J. Non-Cryst. Solids* 425 (2015) 74–82.
3. J. König, R.R. Petersen, Y.Z. Yue, Influence of the glass–calcium carbonate mixture's characteristics on the foaming process and the properties of the foam glass, *J. Eur. Ceram. Soc.* 34 (2014) 1591–1598.